

舗装版切削					
測 点	距 離	表層			備 考
		幅員 (m)	平均幅員 (m)	面積 (m ²)	
NO. 0		5.20			
	20.00		5.145	102.90	
NO. 1		5.09			
	20.00		5.110	102.20	
NO. 2		5.13			
	20.00		5.215	104.30	
NO. 3		5.30			
	20.00		5.250	105.00	
NO. 4		5.20			
	20.00		5.040	100.80	
NO. 5		4.88			
	20.00		5.190	103.80	
NO. 6		5.50			
	20.00		5.385	107.70	
NO. 7		5.27			
	20.00		5.285	105.70	
NO. 8		5.30			
	20.00		5.300	106.00	
NO. 9		5.30			
	20.00		5.310	106.20	
NO. 10		5.32			
	15.50		5.640	87.42	
NO. 10 + 15.50		5.96			
	215.50			1132.02	

舗装版破碎 (t=50)

$$A = (8.15 + 11.82) \times 2.46 / 2 + 5.2 \times 1.65 / 2$$

$$= \boxed{28.85} \text{ m}^2$$

舗装版切削					
測 点	距 離	表層			備 考
		幅員 (m)	平均幅員 (m)	面積 (m ²)	
測 点	距 離	表層			備 考
		幅員 (m)	平均幅員 (m)	面積 (m ²)	
NO. 0		6.00			
	20.00		6.110	122.20	
NO. 1		6.22			
	20.00		6.410	128.20	
NO. 2		6.60			
	20.00		6.145	122.90	
NO. 3		5.69			
	17.00		5.660	96.22	
NO. 3 + 17.00		5.63			
	77.00			469.52	

路面切削

$$A = 1,132.02 + 469.52 = 1,601.54 \text{ m}^2$$

路上路盤再生（t=100）

$$A = 1,132.02 + 28.85 + 469.52 = 1,630.39 \text{ m}^2$$

アスファルト乳剤
MN-1 セメント混合リサイクル用乳剤
セメント系固化剤特殊土用テフロン処理防塵固化剤
デフィックスS

舗装（t=50）

$$A = 1,132.02 + 28.85 + 469.52 = 1,630.39 \text{ m}^2$$

区画線工 数量計算書

計 算 式	数 量
実線・W=15cm・白 29.3+60.5+51.5+53+11.1+60.5	= 265.9 m
破線・W=30cm・白 0.5×18	= 9.0 m
交差点注意・文字等(15cm換算)・白 110.5×2	= 221.0 m